# Kootenay Filter

kootenayfilter.com/product/kfi-3500-with-14-flange/




**KFI 3500 – 14″ x 40″**

Carbon: Granulated Virgin Activated Carbon
Prefilter installed: Yes
Replacement Prefilter SKU: PF3500

**CFM/M3 Ratings:**
Max Exhaust CFM – 1030
Max Recirculate CFM – 2060
Max Exhaust M3 – 1750
Max Recirculating M3 – 3500

SKU: GL3500 Category: Green Line Filters

| | | |
|---|---|---|
| **SKU:** | **GL3500** | |
| Carbon: | Granulated Virgin Activated Carbon | |
| Prefilter Installed: | Yes | |
| Replacement Prefilter SKU: | PF3500 | |
| Measurements and Weights: | Imperial | Metric |
| Outside Diameter: | 17.7" | 45cm |
| Lengths: | 39.4" | 100cm |
| Total Weight: | 64.0lbs | 29kg |
| Carbon Weight: | 35.9lbs | 16.3kg |
| Carbon Bed: | 2.0" | 5.0cm |
| Max Operating Temperature: | 176F | 80°C |
| Minimum Recommended Airflow: | 515CFM | |

| **Possible Fan Combinations:** | **Exhaust** | **Recirculating** |
|---|---|---|
| | Renegade FR 8<br>Renegade FR 10<br>Renegade EC Pro 14<br>Renegade Silent 8<br>Renegade Silent 10 | Renegade FR 12<br>Renegade FR 14<br>Renegade EC Pro 14<br>Renegade Silent 10<br>Renegade Silent 12 |

The Green Line is Kootenay Filter Inc.'s Lightweight Filter Line. KFI is proud to have a product that uses only virgin activated carbon made from renewable resources. The proven design, manufacturing process and a production staff with years of experience make our product one of the best filters on the market. Our Light line filters are available with flange sizes 4″-14″ rated for 3250cfm. Our filters consist of only 2 things, steel and carbon; they are effective and robust.

### Green Line Filters

- Virgin activated carbon made from renewable resources
- Dedusted and screened
- Lightweight filter
- Max operating temperature 80˚C / 176˚F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing

- Single packaged and sealed for storage
- Made in North America
- 2″ carbon bed
- Flanges installed from 4″ to 14″

